YASKAWA

Data sheet
PM 007 - Power-Modul (007-0AA00)

Technical data

Order no.	007-0AA00
Type	PM 007 - Power-Modul
Module ID	-
General information	
Note	-
Features	Power supply DC 24 V (Only electronic module as a spare part for PLC and field bus module)
Technical data power supply	
Input voltage (rated value)	DC 24 V
Input voltage (permitted range)	DC 20.4...28.8 V
I^2t	-
Current consumption (no-load operation)	-
Current consumption (rated value)	-
Max. current drain at backplane bus	-
Max. current consumption load supply	-
Max. current drain load supply	-
Short-circuit protection	-
Efficiency	-
Power loss	1 W
Overvoltage protection	36 V
Status information, alarms, diagnostics	
Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	green LED
Group error display	red LED
Channel error display	none
Housing	
Material	PPE / PPE GF10
Mounting	-
Mechanical data	
Dimensions (WxHxD)	12.9 mm x 58 mm x 62 mm
Net weight	21 g
Weight including accessories	21 g
Gross weight	28 g
Environmental conditions	
Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C
Certifications	

© by Yaskawa Europe GmbH, Philipp-Reis-Str. 6, 65795 Hattersheim, Germany
All data with reservation and subject to change.
Publish date: 07.08.2025

UL certification	yes
KC certification	yes
UKCA certification	yes
ChinaRoHS certification	yes

© by Yaskawa Europe GmbH, Philipp-Reis-Str. 6, 65795 Hattersheim, Germany
All data with reservation and subject to change.
Publish date: 07.08.2025