



SLIO PLC 019-CEFPM00

The new SLIO PLC 019PN, with the article number 019-CEFPM00, is now available! With the PLC 019PN, the system SLIO is extended upwards in the matter of memory and performance and offers the customer a high performance platform for existing applications and future functions and features.

Features

- Including OPC UA server * and WebVisu **
- Including PROFINET IO controller and PROFINET I-Device *
- Including PROFIBUS master/slave *
- PROFINET MRP client and topology recognition
- Programmable with SPEED7 Studio, Simatic Manager and TIA-Portal
- Integrated work memory 6MByte
- PROFINET interface: 2 Ports (as a switch), up to 128 PN devices, up to 24 productive connections,
- PG/OP interface: 2 Ports (as a switch), up to 4 productive connections, DHCP client
- RS485 interface: PROFIBUS master/slave, MPI, USS master, ASCII, STX/ETX, 3964(R), Modbus master/slave

(* = no licenses necessary)

(** = The VIPA SD card 955-0000000 is required to use the OPC-UA server or WebVisu)

For manuals and documentation please refer to
<http://www.vipa.com/en/service-support/manuals/slio/>
<http://www.vipa.com/de/service-support/handbuecher/slio/>

YASKAWA Europe GmbH

Drives Motion Controls

Ohmstr. 4

91074 Herzogenaurach, Germany